


TCL AC

LIGHT COMMERCIAL
HVAC BROCHURE

TCL AC

LIGHT COMMERCIAL SERIES



HIGH EFFICIENCY AND ENERGY SAVINGS/SINGLE ZONE



FULL DC DESIGN

DC inverter compressor and motor ensure increased energy savings and reliability of the system.



SMART DEFROSTING

Precision defrost sensor accurately determines defrost cycle duration allowing the system to provide heat when you need it most.



WIDE TEMPERATURE OPERATION

Standard base pan heater ensures reliable heating operation down from -13°F to 86°F and cooling from 5°F to 133°F.



MULTIPLE PROTECTIONS

Voltage Protection-Overheating Protection-Temperature Protection-Overcurrent Protection-Loss Phase Protection



REFRIGERANT LEAKAGE PROTECTION

If a refrigerant leak occurs, the unit will shut down to prevent further damage to the system.



HOTEL MODE (OPTIONAL)

The AC can be controlled automatically based on the status of doors or windows being opened or closed, and through the fire alarm system for emergency management.



TCL

With a lineup of award-winning televisions, audio products, mobile devices, and HVAC products, TCL delivers meaningful experiences through thoughtful design and the latest technology, helping you enjoy more of the things you love. For more info: hvacsales@tcl.com www.tcl.com/hvac



Single Zone Universal Outdoor - BreezeIN 24 Series


MODEL NUMBER			H09SBH23XPC	H12SBH23XPC	H18SBH22XPC	H24SBH20XPC
System Type			Heat Pump			
SYSTEM PERFORMANCE			SEE INDIVIDUAL INDOOR UNIT SPECIFICATION			
ELECTRICAL						
Power Supply			208-230V / 1Ph / 60Hz			
Voltage Range (Min - Max)		V	187-253			
Rated Current	Cooling	A	3	4.2	6.2	8.3
	Heating	A	3.3	4	6.1	9
Min. Circuit Ampacity - MCA		A	10	10	12	17
Max. Circuit Breaker (MOPA)		A	15	15	20	30
Max. FUSE Size		A	15	15	20	30
Main Power Wire Size		AWG	Per Local Code			
Connection Wiring		AWG	16AWG*4 Stranded, unshielded, TC-ER Type			
Communication Protocol Btwn. IDU & ODU			Current Loop			
REFRIGERANT PIPING						
Refrigerant Type / Charged	oz		R454b / 25.04	R454b / 35.27	R454b / 45.5	R454b / 55.03
Pre-Charge Length Total	ft (m)		25 (7.5)	25 (7.5)	25 (7.5)	25 (7.5)
Additional Charge	oz/ft		0.11	0.11	0.11	0.11
Design Pressure	PSIG		725	725	725	725
Line Set Size (Liquid - Gas)	in		1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8
Line Set Length (Min - Max)	ft (m)		10 - 65 (3 - 20)	10 - 65 (3 - 20)	10 - 82 (3 - 25)	10 - 98 (3 - 30)
Max. Line Set Elevation	ft (m)		33 (10)	33 (10)	50 (15)	65 (20)
OUTDOOR UNIT DATA						
Refrigerant Type			R454b			
Throttle Type			Capillary			
Compressor & Motor Type			INVERTER, DC			
Air Flow	CFM		1,170	1,170	1,890	2,100
Sound Pressure Level	dB(A)		51	53	54.1	59
Cooling Temperature Range	°F (°C)		5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)
Heating Temperature Range	°F (°C)		-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)
External Dimensions (W x H x D)	in		31 7/8 x 21 5/8 x 12	31 7/8 x 21 5/8 x 12	36 1/2 x 27 1/2 x 14 15/16	38 1/2 x 31 5/8 x 16 9/16
	mm		810 x 549 x 305	810 x 549 x 305	927x699x380	978 x 803 x421
Package Dimensions (W x H x D)	in		33 9/16 x 23 5/8 x 14 1/8	33 9/16 x 23 5/8 x 14 1/8	37 13/16 x 28 13/16 x 16	40 1/4 x 32 7/8 x 18 7/8
	mm		852x600 x358	852x600 x358	960 x732 x430	1022x835x480
Weight (Net / Gross)	lbs		52.7 / 59.7	58.4 / 69.4	86 / 93	105.8 / 120.2
	kgs		23.9 / 27.1	26.5 / 31.5	39 / 42.2	48 / 54.5
LIMITED WARRANTY			5 Years Parts, 7 Years Compressor Warranty/10 Year Warranty with Registration within 60 Days of Installation			

TCL AC

LIGHT COMMERCIAL CASSETTE SYSTEM




HIGH EFFICIENCY AND ENERGY SAVINGS/SINGLE ZONE



WIDE RANGE OF SWING ANGLES

Vertical louvers from 0-85 degrees, allowing proper airflow to the room.



47 INCH LIFT PUMP

Built in pump provides up to 47 inches of lift for proper condensate drainage.



EASY TO CLEAN FILTER

An easily accessible filter allows for quick maintenance and efficient operation.



WATER-FILLED PROTECTION

Condensate overflow protection shuts down the system to stop water damage before it occurs.




TCL

With a lineup of award-winning televisions, audio products, mobile devices, and HVAC products, TCL delivers meaningful experiences through thoughtful design and the latest technology, helping you enjoy more of the things you love. For more info: hvacsales@tcl.com www.tcl.com/hvac

Light Commerial Cassette System - Single Zone (with BreezeIN 24 Series ODU)						
MODEL NUMBER - IDU			H09CSHU1XAE	H12CSHU1XAE	H18CSHU1XAE	H24CSHU1XAE
MODEL NUMBER - ODU			H09SBH23XPC	H12SBH23XPC	H18SBH22XPC	H24SBH20XPC
System Type			Heat Pump			
SYSTEM PERFORMANCE						
AHRI Certificate			215570370	215570372	215570374	215570376
Cooling at 95°F (35°C)	Capacity (Min - Max)	BTU/h	9,500(2,000-10,400)	12,000(2,000-13,600)	16,000(6,000-19,400)	23,000(7,500-25,200)
	Rated Input Power	W	750	1,030	1,365	2,000
	Rated Current	A	4.9	6.3	6.3	11.3
	SEER2 / EER2		22 / 12	21 / 11.7	20 / 11.7	22 / 11.7
Heating at 47°F (8.3°C)	Capacity (Min - Max)	BTU/h	10000(2,500-12,500)	12000(3,100-12,700)	18000(4,000-18,000)	25000(8,700-28,300)
	Rated Input Power	W	720	1,030	1,640	1,960
	Rated Current	A	4.7	4.7	7.6	11.7
	HSPF2 / COP		10/ 4.2	10 / 3.8	8.5 / 3.2	10 / 3.35
Heating at 17°F (-8.3°C)	Rated Capacity	BTU/H	6,300	7,800	11,000	15,300
Heating at 5°F (-15°C)	Max. Capacity	BTU/h	7,800	9,200	13,400	19,200
	COP		1.95	1.90	1.76	2.00
ENERGY STAR® Certified			YES	YES	YES	YES
Ambient Temperature Range	Cooling	°F (°C)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)
	Heating	°F (°C)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)
ELECTRICAL						
Power Supply			208 -230V / 1Ph / 60Hz			
Voltage Range (Min - Max)			187 - 253			
Min. Circuit Ampacity - MCA		A	10	10	11	15
Max. Circuit Breaker (MOCP)		A	15	15	17	20
Max. FUSE Size		A	15	15	17	20
Main Power Wire Size		AWG	Per Local Code			
Connection Wiring		AWG	16AWG*4 Stranded, unshielded, TC-ER Type			
REFRIGERANT PIPING						
Refrigerant Type / Charged		oz	R454b / 25.04	R454b / 35.27	R454b / 45.5	R454b / 55.03
Pre-Charge Length Total		ft (m)	25 (7.5)	25 (7.5)	25 (7.5)	25 (7.5)
Additional Charge		oz/ft	0.11	0.11	0.11	0.11
Design Pressure		PSIG	600	600	600	600
Line Set Sized (Liquid - Gas)		in	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8
Line Set Length (Min - Max)		ft (m)	16 - 50 (5 - 15)	16 - 50 (5 - 15)	16 - 65 (5 - 20)	16 - 65 (5 - 20)
Max. Pipe Elevation		ft (m)	33 (10)	33 (10)	49 (15)	49 (15)
INDOOR UNIT DATA						
Indoor Motor Type			DC			
Thermostat type			Wireless Remote Controller with Wi-Fi® & Voice Control			
Air Flow (Tu/Hi/Mi/Lo/Mu)		CFM	329/300/270/217/194	360/320/260/200/190	423/394/335/282/252	836/765/630/530/482
Sound Pressure Level (Tu/Hi/Mi/Lo/Mu)		dB(A)	43/41/37/33/32	45/43/39/35/32	48/46/42/39/37	51/48/44/40/37
External Dimensions (W x H x D)		in	22 7/16 x 9 5/8 x 22 7/16	22 7/16 x 9 5/8 x 22 7/16	22 7/16 x 9 5/8 x 22 7/16	33 1/16 x 10 1/16 x 33 1/16
		mm	570 x 245 x 570	570 x 245 x 570	570 x 245 x 570	840 x 255 x 840
Package Dimensions (W x H x D)		in	28 1/4 x 11 7/8 x 25 7/8	28 1/4 x 11 7/8 x 25 7/8	28 1/4 x 11 7/8 x 25 7/8	36 7/8 x 11 7/16 x 36 7/8
		mm	718 x 301 x 657	718 x 301 x 657	718 x 301 x 657	935 x 290 x 935
Weight (Net / Gross)		lbs	32 / 38.6	32 / 38.6	32 / 38.6	51.8 / 60.6
		kgs	14.5 / 17.5	14.5 / 17.5	14.5 / 17.5	23.5 / 27.5
OUTDOOR UNIT DATA						
Compressor Type			Inverter			
Motor Type			DC			
Throttle type			Capillary			
Air Flow (Max.)		CFM	1,170	1,170	1,890	2,100
Sound Pressure Level		dB(A)	54	56	59	61
External Dimensions (W x H x D)		in	31 7/8 x 21 5/8 x 12	31 7/8 x 21 5/8 x 12	36 1/2 x 27 1/2 x 14 15/16	38 1/2 x 31 5/8 x 16 9/16
		mm	810 x 549 x 305	810 x 549 x 305	927x699x380	978x803 x421
Package Dimensions (W x H x D)		in	33 9/16 x 23 5/8 x 14 1/8	33 9/16 x 23 5/8 x 14 1/8	37 13/16 x 28 13/16 x 16 15/16	40 1/4 x 32 7/8 x 18 7/8
		mm	852x600 x358	852x600 x358	960 x732 x430	1022x835x480
Weight (Net / Gross)		lbs	52.7 / 59.7	58.4 / 69.4	86 / 93	104.7 / 125.7
		kgs	23.9 / 27.1	26.5 / 31.5	39 / 42.2	47.5 / 57
PANEL ACCESSORY DATA (Packed Separately)			Cassette Panel 01	Cassette Panel 01	Cassette Panel 01	Cassette Panel 02
External Dimensions (W x H x D)		in	25 9/16 x 2 3/8x 25 9/16	25 9/16 x 2 3/8x 25 9/16	25 9/16 x 2 3/8x 25 9/16	37 3/8 x 2 7/8 x 37 3/8
		mm	650 x 60 x 650	650 x 60 x 650	650 x 60 x 650	950 x 73 x 950
Package Dimensions (W x H x D)		in	28 15/16 x 4 5/16 x 28 15/16	28 15/16 x 4 5/16 x 28 15/16	28 15/16 x 4 5/16 x 28 15/16	41 9/16 x 3 9/16 x 41 9/16
		mm	735 x 110 x 735	735 x 110 x 735	735 x 110 x 735	1055 x 90 x 1055
Weight (Net / Gross)		lbs	6 / 9.5	6 / 9.5	6 / 9.5	13.2 / 19.8
		kgs	2.7 / 4.3	2.7 / 4.3	2.7 / 4.3	6 / 9
LIMITED WARRANTY			5 Years Parts, 7 Years Compressor Warranty/10 Year Warranty with Registration within 60 Days of Installation			

LIGHT COMMERCIAL SLIM DUCT SYSTEM




HIGH EFFICIENCY AND ENERGY SAVINGS/SINGLE ZONE




QUIET OPERATION

High efficiency DC fan motor and optimized air duct design enables 35dB quiet operation.




47 INCH LIFT PUMP

Built in pump provides up to 47 inches of lift for proper condensate drainage.



7.88 INCH ULTRA-THIN DESIGN

The ultra-thin body of 7.88 inches greatly saves the installation area and can match a variety of interior design styles.



FLEXIBLE RETURN AIR INTAKE

Standard built return air box can be mounted for horizontal or bottom return.



Light Commercial Slim Duct System - Single Zone (with BreezeIN 24 Series ODU)

MODEL NUMBER - IDU			H09DTHU1XAE	H12DTHU1XAE	H18DTHU1XAE	H24DTHU1XAE
MODEL NUMBER - ODU			H09SBH23XPC	H12SBH23XPC	H18SBH22XPC	H24SBH20XPC
System Type			Heat Pump			
SYSTEM PERFORMANCE						
AHRI Certificate			215570371	215570373	215570375	215570377
Cooling at 95°F (35°C)	Capacity (Min - Max)	BTU/h	9,500 (2,000 - 10,400)	11,000 (2,000 - 12,300)	17,000 (6,000 - 19,400)	22,000 (7,550 - 24,600)
	Rated Input Power	W	750	940	1,450	1,870
	Rated Current	A	4.9	6.2	6.4	11.2
	SEER2 / EER2		20.5 / 12.5	19 / 11.7	21 / 11.7	19 / 11.7
Heating at 47°F (8.3°C)	Capacity (Min - Max)	BTU/h	10,000 (2,500 - 12,300)	12,000 (3,100 - 12,300)	18,000 (4,000 - 21,400)	25,000 (8,700 - 28,500)
	Rated Input Power	W	800	1,030	1,805	2,030
	Rated Current	A	5.2	5.2	8.3	13.3
	HSPF2 / COP		9.5 / 3.7	8.1 / 3.5	8.1 / 2.9	9.5 / 3.45
Heating at 17°F (-8.3°C)	Rated Capacity	BTU/H	6,100	7,500	11,000	15,100
Heating at 5°F (-15°C)	Max. Capacity	BTU/h	7,600	8,900	13,400	19,300
	COP		1.85	1.80	1.78	2.00
ENERGY STAR® Certified			YES	YES	YES	YES
Ambient Temperature Range	Cooling	°F (°C)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)
	Heating	°F (°C)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)
ELECTRICAL						
Power Supply			208-230V / 1Ph / 60Hz			
Voltage Range (Min - Max)			187 - 253			
Min. Circuit Ampacity - MCA		A	10	10	11	15
Max. Circuit Breaker (MOCP)		A	15	15	17	20
Max. FUSE Size		A	15	15	17	20
Main Power Wire Size		AWG	Per Local Code			
Connection Wiring		AWG	16AWG*4 Stranded, unshielded, TC-ER Type			
REFRIGERANT PIPING						
Refrigerant Type / Charged		oz	R454b / 25.04	R454b / 35.27	R454b / 45.5	R454b / 55.03
Pre-Charge Length Total		ft (m)	25 (7.5)	25 (7.5)	25 (7.5)	25 (7.5)
Additional Charge		oz/ft	0.11	0.11	0.11	0.11
Design Pressure		PSIG	600	600	600	600
Line Set Sized (Liquid - Gas)		in	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8
Line Set Length (Min - Max)		ft (m)	16 - 50 (5 - 15)	16 - 50 (5 - 15)	16 - 65 (5 - 20)	16 - 65 (5 - 20)
Max. Pipe Elevation		ft (m)	33 (10)	33 (10)	49 (15)	49 (15)
INDOOR UNIT DATA						
Indoor Motor Type		DC				
Thermostat type		Programmable Wired Controller with Wi-Fi® & Voice Control				
Air Flow (Tu/Hi/Mi/Lo/Mu)		CFM	335/305/276/182/182	360/330/270/210/180	500/426/370/300/247	741/623/558/529/470
Sound Pressure Level (Tu/Hi/Mi/Lo/Mu)		dB(A)	42/39/34/28/28	44/41/35/33/32	48/44/41/36/33	51/49/46/39/34
External Dimensions (W x H x D)	in	27 9/16 x 7 7/8 x 19 5/16	27 9/16 x 7 7/8 x 19 5/16	36 1/4 x 7 7/8 x 19 5/16	43 5/16 x 7 7/8 x 19 3/10	
	mm	700 x 200 x 490	700 x 200 x 490	920 x 200 x 490	1100 x 200 x 490	
Package Dimensions (W x H x D)	in	35 7/16 x 9 13/16 x 21 7/8	35 7/16 x 9 13/16 x 21 7/8	44 1/8 x 9 13/16 x 21 7/8	50 13/16 x 9 5/8 x 22 1/4	
	mm	900 x 250 x 555	900 x 250 x 555	1120 x 50 x 555	1290 x 245 x 565	
Weight (Net / Gross)	lbs	33.1 / 40.8	33.1 / 40.8	39.7 / 46.3	50.7 / 58.4	
	kgs	15 / 18.5	15 / 18.5	18 / 21	23 / 26.5	
OUTDOOR UNIT DATA						
Compressor Type		Inverter				
Motor Type		DC				
Throttle type		Capillary				
Air Flow (Max.)		CFM	1,170	1,170	1,890	2,100
Sound Pressure Level		dB(A)	54	56	59	61
External Dimensions (W x H x D)	in	31 7/8 x 21 5/8 x 12	31 7/8 x 21 5/8 x 12	36 1/2 x 27 1/2 x 14 15/16	38 1/2 x 31 5/8 x 16 9/16	
	mm	810 x 549 x305	810 x 549 x 305	927 x 699 x 380	978 x 803 x 421	
Package Dimensions (W x H x D)	in	33 9/16 x 23 5/8 x 14 1/8	33 9/16 x 23 5/8 x 14 1/8	37 13/16 x 28 13/16 x 16 15/16	40 1/4 x 32 7/8 x 18 7/8	
	mm	852 x 600 x 358	852 x 600 x 358	960 x 732 x 430	1022 x 835 x 480	
Weight (Net / Gross)	lbs	52.7 / 59.7	58.4 / 69.4	86 / 93	104.7 / 125.7	
	kgs	23.9 / 27.1	26.5 / 31.5	39 / 42.2	47.5 / 57	
LIMITED WARRANTY		5 Years Parts, 7 Years Compressor Warranty/10 Year Warranty with Registration within 60 Days of Installation				

TCL AC

LIGHT COMMERCIAL FLOOR & CEILING SYSTEM




HIGH EFFICIENCY AND ENERGY SAVINGS/SINGLE ZONE




FLEXIBLE INSTALLATION

Convertible to floor or under ceiling application allows for design flexibility.



ULTRA-THIN DESIGN

Compact 9.25-inch depth (floor mount) or height (ceiling mount) design requires minimal space for installation.



80° WIDE RANGE OF AIR FLOW

With our unique louver design, the air flow can be adjusted to provide uniform air distribution.



DUAL DRAINAGE

Condensate drain flexibility allows for left-side or right-side piping.



TCL

With a lineup of award-winning televisions, audio products, mobile devices, and HVAC products, TCL delivers meaningful experiences through thoughtful design and the latest technology, helping you enjoy more of the things you love. For more info: hvacsales@tcl.com www.tcl.com/hvac

Light Commercial Floor Ceiling System - Single Zone (with BreezeIN 24 Series ODU)

MODEL NUMBER - IDU			H18FCHU1XAE	H24FCHU1XAE
MODEL NUMBER - ODU			H18SBH22XPC	H24SBH20XPC
System Type			Heat Pump	
SYSTEM PERFORMANCE				
AHRI Certificate			216741387	216741386
Cooling at 95°F (35°C)	Capacity (Min - Max)	BTU/h	18,000 (6,000 - 20,200)	22,200 (7,550 - 24,600)
	Rated Input Power	W	1,510	1,920
	Rated Current	A	6.8	11.4
	SEER2 / EER2		20.5 / 11.7	20 / 11.7
Heating at 47°F (8.3°C)	Capacity (Min - Max)	BTU/h	19,000 (4,000 - 21,400)	24,400 (8,700 - 28,500)
	Rated Input Power	W	1,720	2,100
	Rated Current	A	7.7	11.9
	HSPF2 / COP		9 / 3.30	9.5 / 3.46
Heating at 17°F (-8.3°C)	Rated Capacity	BTU/H	11,400	14,400
Heating at 5°F (-15°C)	Max. Capacity	BTU/h	13,800	19,200
	COP		1.85	2
ENERGY STAR ®			YES	YES
ENERGY STAR ® with Cold Climate			YES	YES
Ambient Temperature Range	Cooling	°F (°C)	5 - 133 (-15 - 55)	5 - 133 (-15 - 55)
	Heating	°F (°C)	-13 - 86 (-25 - 30)	-13 - 86 (-25 - 30)
ELECTRICAL				
Power Supply			208-230V / 1Ph / 60Hz	
Voltage Range (Min - Max)			187 - 253	
Min. Circuit Ampacity - MCA		A	11	15
Max. Circuit Breaker (MOCP)		A	17	20
Max. FUSE Size		A	17	20
Main Power Wire Size		AWG	Per Local Code	
Connection Wiring		AWG	16AWG*4 Stranded, unshielded, TC-ER Type	
REFRIGERANT PIPING				
Refrigerant Type / Charged		oz	R454b / 45.5	R454b / 55.03
Pre-Charge Length Total		ft (m)	25 (7.5)	25 (7.5)
Additional Charge		oz/ft	0.11	0.11
Design Pressure		PSIG	600	600
Line Set Sized (Liquid - Gas)		in	1/4 - 1/2	1/4 - 5/8
Line Set Length (Min - Max)		ft (m)	16 - 65 (5 - 20)	16 - 65 (5 - 20)
Max. Pipe Elevation		ft (m)	49 (15)	49 (15)
INDOOR UNIT DATA				
Indoor Motor Type			DC	
Thermostat type			Wireless Remote Controller with Wi-Fi® & Voice Control	
Air Flow (Min - Max)		CFM	353 - 588	470 - 647
Sound Pressure Level (Min - Max)		dB(A)	36 - 50	40 - 53
External Dimensions (W x H x D)		in	41 1/2 x 26 9/16 x 9 1/4	41 1/2 x 26 9/16 x 9 1/4
		mm	1055 x 675 x 235	1055 x 675 x 235
Package Dimensions (W x H x D)		in	44 11/16 x 30 1/8 x 11 1/16	44 11/16 x 30 1/8 x 11 1/16
		mm	1135 x 765x 280	1135 x 765x 280
Weight (Net / Gross)		lbs	52.9/ 68.2	55.0 / 70.4
		kgs	24 / 31	25 /32
OUTDOOR UNIT DATA				
Compressor Type			Inverter	
Motor Type			DC	
Throttle type			Capillary	
Air Flow (Max.)		CFM	1,890	2,100
Sound Pressure Level		dB(A)	59	61
External Dimensions (W x H x D)		in	36 1/2 x 27 1/2 x 14 15/16	38 1/2 x 31 5/8 x 16 9/16
		mm	927x 699 x 380	978 x 803 x 421
Package Dimensions (W x H x D)		in	37 13/16 x 28 13/16 x 16 15/16	40 1/4 x 32 7/8 x 18 7/8
		mm	960 x 732 x 430	1022 x 835 x 480
Weight (Net / Gross)		lbs	86 / 93	104.7 / 125.7
		kgs	39 / 42.2	47.5 / 57
LIMITED WARRANTY	5 Years Parts, 7 Years Compressor Limited Warranty / 10 Years Warranty with Registration within 60 Days of Installation			

©2025 TCL North America. All rights reserved.

TCL and TCL AC are trademarks of TCL North America. All the other product names mentioned herein are trademarks or registered trademarks of their respective owners.

Use of the AHRI Certified® mark indicates a manufacturer's participation in the certification program. For verification of certification for individual products, go to www.ahridirectory.org.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the United States Environmental Protection Agency.

Specifications shown in this brochure are subject to change without notice. View complete warranty certificate for terms, conditions and limitations. A copy is available from TCL North America.

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION, DESIGN OR OTHERWISE.

TCL North America, its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

The first part of the paper discusses the importance of the research and the objectives of the study. It then presents a literature review of the existing research on the topic. The next section describes the methodology used in the study, including the data sources and the statistical techniques employed. The results of the study are then presented, followed by a discussion of the findings and their implications. The paper concludes with a summary of the main points and suggestions for further research.

The research was conducted using a combination of primary and secondary data. Primary data was collected through a series of interviews with experts in the field, while secondary data was obtained from a review of the existing literature. The data was then analyzed using a range of statistical techniques, including regression analysis and factor analysis.

The findings of the study indicate that there is a significant relationship between the variables studied. The results suggest that the factors identified in the study are important in explaining the variation in the dependent variable. The implications of these findings are discussed in the context of the existing literature and the practical application of the research.

In conclusion, the study has provided valuable insights into the relationship between the variables studied. The findings have important implications for both theory and practice, and suggest areas for further research.

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000